



Functions

- Weighing, Action-Tare-Memory, Piece Counting, Peak Hold, Animal Weighing
- Near Zero Weight Value for Dynamic Weighing to avoid False Signal Output
- Auto, Manual, Pre-set, Repetitive & Continuous Tare Operation
- 10 x Quick Access PLUs for Lo/Hi Limit and Preset Tare for each Weight Unit
- 10 x Direct Access PLUs for Product Code
- 1 x Configurable Optical Key for either Tare, Zero or Print/M+
- Weight and Quantity Check Mode
- Check Result Control for Accumulation, Data Printout & Data Output
- Keypad Lock Function

Indicator Features

- Product Code Input through Serial Scanner or Keypad
- Configurable Tri-Color Check Result Light Bar
- 70 hours plus Battery Service Time
- Full Numeric Keypad
- Configurable Keypad, Check & System Buzzer
- 2 x Independently Configurable Bi-Direction Serial Comports
- Configurable Machine ID and Group Number to Enhance Ease of Multi-Scales Applications
- All Current Operation Results Output in Data Base Format Increases Ease & Efficiency of Data Management, Processing & Analysis
- Ticket Printing and Label Printing (LP-50, TDP247, TDP345, TTP247, TTP345 Label Printer)
- Selectable Portrait / Landscape Ticket Printout Format
- Maximum Calibration Points Required = 3 (Zero, Linearity Point 1 and 2); Independent Zero and Linearity Point Calibration
- Zero, Net, Weight Unit, Memory & Lo Battery Level & Recharge Status Indicators
- Real Time Clock



Platform Features

- Epoxy Coated Heavy Duty Q235 Mild Steel Structure
- Safe Overload = 150%
- Ultimate Overload = 300%
- #304 Stainless Steel Platform Cover with Noise Absorption Layer
- Overload and Transportation Protection Device

Versatility, Functionality and Accuracy are always Built-in

19eA+KS Heavy Duty Bench Scales Series

Specifications

Model No.	Capacity & Division (kg)		Platform Dimensions
	Max	d	
19eA+KS-B30	30	0.001	330 x 450mm
19eA+KS-B60	60	0.002	
19eA+KS-B150	150	0.005	
19eA+KS-F30	30	0.001	420 x 520mm
19eA+KS-F60	60	0.002	
19eA+KS-F150	150	0.005	
19eA+KS-F300	300	0.01	
19eA+KS-F600	600	0.05	
19eA+KS-L30	30	0.001	500 x 600mm
19eA+KS-L60	60	0.002	
19eA+KS-L150	150	0.005	
19eA+KS-L300	300	0.01	
19eA+KS-L600	600	0.05	
19eA+KS-XL60	60	0.002	600 x 800mm
19eA+KS-XL150	150	0.005	
19eA+KS-XL300	300	0.01	
19eA+KS-XL600	600	0.05	
Weight Units	kg, g, lb		
Display	6 x 25mm LED Numeric Digits		
Load Cell Connection	- Excitation Voltage = 5V DC - Support both 4-wire & 6-wire Load Cells - Maximum Load Cell Connection = 12 x 350Ω Load Cells or 24 x 700Ω Load Cells		
A/D Converter & Internal Resolution	24 bit Low-Noise Delta to Sigma ($\Delta-\Sigma$) 4,000,000 Counts at 20 mV - Minimum input per d = 0.05μV		
Max. Tare Range	-Max or -Max ₁ (Subtractive Tare)		
Power Source	- Built-in Rechargeable Battery = 6V, 4AH - External Power Adaptor = DC 12V, 1A		
Accessories	Built-in Rechargeable Battery, Universal Power Adaptor, Indicator Dust Cover, Pillar, Adjustable Feet and Bubble Level		
Packing	Individually Packed. Dimensions and Weights - With B Platform: - 71 x 56 x 22cm. Net / Gross = 12.50 / 15.00kg - With F Platform: - 88 x 57 x 24cm. Net / Gross = 20.00 / 22.50kg - With L Platform: - 106 x 75 x 26cm. Net / Gross = 26.50 / 30.00kg - With XL Platform: - 121 x 84 x 26cm. Net / Gross = 35.5 / 40.00kg		
Operation Environment	-10 ~ 40°C. Non-condensed. R.H. ≤ 85%		

In the interest of improvement, specifications may change prior to notice

Versatility, Functionality and Accuracy are always Built-in

19eA+KS Heavy Duty Bench Scales Series

Options

- Stainless Steel Wall/Desk Mount Holder
- Secondary Comport
- SP-POS58IV & SP-POS88IV Thermal Ticket Printer
- LP-50, TDP247, TDP345, TTP247, TTP345 Label Printer
- Serial Bar Code Scanner
- WM Wireless Communication Module
- RD-DOT Dot Matrix Remote Display



Fidelity Measurement Co., Ltd.
<http://www.fi-measurement.com>
e-mail: info@fi-measurement.com

REV.: 19eA+KS/18/01/01